

t³ec	Job No.	Referring Dwg No.:		Location:				Prepared By:		Date:		Sheet:	Status:
	J2783	02		Ground Beams - Plot 2				TC		26.03.18		1	C
Project:								Checked By:		Date:		Revision:	Date:
65 High Street, Upwood, PE26 2QE								DT		24.04.18			
Member	Bar Mark	Type & Size	No. of Mbrs	No. in each	Total No.	Length of each bar + mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/r* mm	
GB1 & GB3	01	H8	2	31	62	1575	51	360	350	(115)	(115)		
	02	H8		31	62	600	22	115	350	50	(115)		
	21	H12		6	12	1000	11	125	(890)				
	22	H16		6	12	1150	11	130	(1050)				
	23	H12		3	6	5375	00	STR					
	24	H16		3	6	5375	00	STR					
	25	H12		3	6	1425	00	STR					
	26	H16		3	6	1750	00	STR					
	27	H12		3	6	2500	00	STR					
	28	H16		3	6	2500	00	STR					
	29	H8		2	4	2175	51	360	650	(115)	(115)		
GB2 & GB4	01	H8	2	23	46	1575	51	360	350	(115)	(115)		
	02	H8		23	46	600	22	115	350	50	(115)		
	21	H12		6	12	1000	11	125	(890)				
	22	H16		6	12	1150	11	130	(1050)				
	30	H12		3	6	6125	00	STR					
	31	H16		3	6	6125	00	STR					

All Bending Dimensions Are In Accordance With BS.8866
 * Specified To The Nearest 5mm + Specified To The Nearest 25mm

t³ec	Job No.	Referring Dwg No.:			Location:			Prepared By:		Date:		Sheet:	Status:
	J2783	02			Ground Beams - Plot 2			TC		26.03.18		2	C
Project:								Checked By:		Date:		Revision:	Date:
65 High Street, Upwood, PE26 2QE								DT		24.04.18			
Member	Bar Mark	Type & Size	No. of Mbrs	No. in each	Total No.	Length of each bar + mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/r* mm	
GB5, & GB10	01	H8	2	30	60	1575	51	360	350	(115)	(115)		
	02	H8		30	60	600	22	115	350	50	(115)		
	21	H12		6	12	1000	11	125	(890)				
	22	H16		6	12	1150	11	130	(1050)				
	25	H12		3	6	1425	00	STR					
	26	H16		3	6	1750	00	STR					
	37	H12		6	12	3975	00	STR					
	38	H16		6	12	3975	00	STR					
GB6, GB7, GB8, & GB9	01	H8	4	30	120	1575	51	360	350	(115)	(115)		
	02	H8		30	120	600	22	115	350	50	(115)		
	21	H12		6	24	1000	11	125	(890)				
	25	H12		3	12	1425	00	STR					
	32	H20		6	24	1350	11	190	(1200)				
	34	H20		3	12	2050	00	STR					
	37	H12		6	24	3975	00	STR					
	39	H20		6	24	3975	00	STR					

All Bending Dimensions Are In Accordance With BS.8866
 * Specified To The Nearest 5mm + Specified To The Nearest 25mm